


### PRINTER TYPES



### FLAME RETARDANT STANDARDS



### APPLICATIONS

Banners. Displays frame systems.  
Signage.



Photo courtesy of Embrace Building Wraps, UK

PROPERTIES	TEST METHOD	RESULT	UNIT
Weight		360 ± 20	gsm
Thickness		0.37 ± 0.02	mm
Regular roll length		50	metres
Max Width	DIN EN ISO 2286-1	5	metres
Composition	Polyester yarn • PVC-free coating		
Coating	Water-based • Phthalate free		
Characteristics	Lightweight • Directly weldable • Perfect for high quality digital printing		
Tensile Strength (W/F)	DIN 53354	280/250	Kg/5cm
Tear Resistance (W/F)	DIN 53363	33/30	Kg
Temperature Range	DIN 53361	-40~+90	°C

\*Test data is for reference only and may vary according to usage.\*



No. 777 Fengguan Road, Fengjing Industrial Park,  
Jinshan District, Shanghai, China. Post Code:201501  
TEL: +86-21-6463 2409  
FAX: +86-21-6463 2157  
EMAIL: info@goforkavalan.com  
WEB : www.goforkavalan.com



Greenhouse gas emissions of packaged PVC-free Kavalan banner (model Sunlight Weldable) for industrial application are **1.7 kgCO<sub>2</sub>e** per 1 square meter (m<sup>2</sup>) unit. The calculation is based on the data collected from January 2020 to September 2020 from cradle to grave.  
SGS Report No. **LCA20123-14**