

## Perforated Vinyl Technical Information

Specification	Description	
<b>PVC</b>	Type	Calendered polymeric soft PVC film
	Thickness	180±10um
	Color Code	Ceramic white
	Back	Black
	Shrinkage	/ 0.6%
	Surface Tension	0 30dn/cm
	Opacity	>99%
	Holes No.	Average 130/sq in
	Hole Diameter	1.62mm
	Distance Between Holes	Left-right 1.25mm Up-down 2.0mm
	Hole Space	40%
<b>Adhesive</b>	Type	Clear solvent based removable pressure sensitive glue
	Weight(g/1 )	35 ± 5
	Adhesion Temperature	10℃~40℃
	180° Peeling Force	0 4N/25mm 24H （参照 FTM1）
	Initial Adhesion- Ball Tack	0 2N/25MM*25MM （参照 FTM9）
	Holding Power	0 1440min （参照 FTM8）
	Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23~25℃ and RH of 50~60%
<b>Liner</b>	Type	Laminaed OPP Film
	Color	Clear
	Weight	90g±10g/1
	Release Force	0.05~0.20N/25MM
<b>Storage Period</b>	12 months under ordinary condition at temperature of 22℃ and relative humidity of 50-55%	

<b>Application</b>	One way vision: Outdoor digital and silk screen printing media for vehicle graphics, airport graphics, subway window, platform graphics, glass walls of building and signage display applications.
<b>Compatibility of machines and ink</b>	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original inks from the printer manufacturers. The best printing temperature is 35-40°C.